

# RUBBERWORX

## 600 PSI WIRE AIR BRAID



This heavy duty wire reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications. The ozone and abrasion resistant cover holds up to the toughest applications

<b>TUBE:</b>	SYNTHETIC NR
<b>REINFORCEMENT:</b>	2 HIGH TENSILE STEEL BRAIDED WIRES
<b>COVER:</b>	OZONE RESISTANT SYNTHETIC RUBBER
<b>TEMPERATURE:</b>	-22°F to 275°F
<b>BRANDING:</b>	600 PSI WIRE AIR BRAID
<b>PACKAGING SPECIFICATIONS:</b>	50', 100' COILS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
5004103-050	0.50	0.80	600	2400	4	NA	0.44	50', 100'
5004103-075	0.75	1.10	600	2400	6	NA	0.75	50', 100'
5004103-100	1.00	1.45	600	2400	8	NA	1.16	50', 100'
5004103-125	1.25	1.80	600	2400	10	NA	1.40	50', 100'
5004103-150	1.50	2.00	600	2400	12	NA	1.57	50', 100'
5004103-200	2.00	2.50	600	2400	15	NA	1.95	50', 100'
5004103-250	2.50	3.05	600	2400	22	NA	2.65	50', 100'
5004103-300	3.00	3.70	600	2400	35	NA	3.95	50', 100'
5004103-400	4.00	5.00	600	2400	45	NA	5.95	50', 100'
5004103-600	6.00	6.95	600	2400	75	NA	8.35	50', 100'